


Built on Leadership








Features EcoSafe Range

- Double skinned construction bunded area holds 110% of inner capacity.
- Low maintenance no rust and no painting.
- SpillStop overfill prevention device fitted as standard. This device shuts off once fuel reaches 95% of the tank volume.
- Lockable lid.
- EcoSafe tanks are fitted with a bottom outlet and the contents of the tank pack come with a unique gate valve and filter supplied as standard.
- Comes complete with WatchMan Alarm tank pack and ultrasonic oil level monitor.
- EcoSafe tanks are made from recyclable polyethylene.
- Top outlet options are available on the tanks to further reduce the risk of spillage.

WatchMan Alarm

How it works



Transmitter measures the level of oil in the tank.

It transmits that information to the receiver plugged into an electronic wall socket in the building.

Liquid level is displayed on a LCD screen on the receiver.

When the level of oil gets below 10% the fuel dispensing symbol appears, indicating to the owner that they need to order oil.

In the event of the oil level dropping at a dramatic rate (more than 1.5cm a minute) the receiver will emit an audible alarm.





EcoSafe Horizontal 1,000 - 2,500 litres



EcoSafe Slimline 1,000 - 4,000 litres



EcoSafe Vertical 1,300 - 9,000 litres

The Benefits

Safe and Robust Oil Storage Solutions

EcoSafe Range offers:

Slimline models

The slimline bunded EcoSafe oil storage tanks are the perfect solution for locations with limited space and access restrictions. The slimline models have a smaller footprint than standard oil tanks making it much easier to manoeuvre and fit into tight spaces. Available in capacities 1000, 1400, 2000 and 4000 litres.



Double skinned construction

EcoSafe tanks come double skinned for environmental protection and to safeguard against leaks and ground contamination. Our tanks comply with all national oil storage regulations*.



Security

EcoSafe tanks come as standard with the WatchMan Alarm oil level monitor which reduces the possibility of running out of fuel and deterring theft whilst also giving you security and peace of mind.



Reliability

Kingspan is known for excellent service, quality products and trustworthy guarantees combined with over 40 years experience you know you can trust.



Industry Approved

All EcoSafe tanks are CE marked, OFTEC approved and fully compliant with current regulations and safety standards.





Service

We pride ourselves on a quality customer experience from a comprehensive free on-site survey, professional installation options, full technical and after sales support and fast delivery times.



Slimline

Intelligence Inside








TITAN EcoSafe®

3 Easy steps to the perfect Oil storage solution



Step 01

be required.





Local engineer will advise you on which tank is most suitable for your property and ensure you comply with regulations.



Step 03



Once your tank is installed, send us back your warranty card or complete your online registration at www.kingspan.co.uk/environmental-guarantee.

*England and Wales - The Control of Pollution (Oil Storage) Regulations 2001. Scotland - The Water Environment (Oil Storage Scotland) Regulations 2006. Northern Ireland - The Building (Amendment) Regulations (Northern Ireland) 2006.

-

Models and Specifications

Choose your shape and size from 1,000 - 9,000 litres, with our complete range of EcoSafe bunded oil tanks



ESSL1000

| Capacity | Length | Width | Height |
|------------------------|---------|--------|---------|
| 1000 Ltrs/ 220 Gals | 1920 mm | 600 mm | 1580 mm |



ES1000

| Capacity | Length | Width | Height |
|------------------------|---------|--------|---------|
| 1000 Ltrs/ 220 Gals | 2150 mm | 690 mm | 1480 mm |



ES1300

| Capacity | Length | Width | Height |
|------------------------|---------|---------|---------|
| 1300 Ltrs/ 285 Gals | 1920 mm | 1230 mm | 1300 mm |



ESV1300

| Capacity | Diameter | Height |
|------------------------|----------|---------|
| 1300 Ltrs/ 285 Gals | 1550 mm | 1485 mm |



ESSL2000

| Capacity | Length | Width | Height |
|------------------------|---------|--------|---------|
| 2000 Ltrs/ 440 Gals | 2500 mm | 800 mm | 1650 mm |



ES2500

| Capacity | Length | Width | Height |
|------------------------|---------|---------|---------|
| 2500 Ltrs/ 550 Gals | 2450 mm | 1425 mm | 1450 mm |



ESSL4000

| Capacity | Length | Width | Height |
|------------------------|---------|---------|---------|
| 4000 Ltrs/ 800 Gals | 3170 mm | 1150 mm | 2340 mm |

(Top outlet only)



ES5000

| Capacity | Diameter | Height |
|-------------------------|----------|---------|
| 5000 Ltrs/ 1100 Gals | 2250 mm | 2400 mm |

WatchMan Alarm | Tank Pack for EcoSafe Tanks

WATCH

All EcoSafe tanks come complete with a WatchMan Alarm tank pack greatly reducing installation time and providing electronic measurement for you the user.

Tank Pack consists of:

1. WatchMan Alarm Transmitter

2. WatchMan Alarm Receiver 5

3. PTFE Tape

5. Heldlite Application6. Gate Valve and Filter



Suitable for the storage of Kerosene (C1/C2), Fuel Oil (A2), and gas oil/diesel, as defined in BSEN2869 and BSEN590, including up to 7% biofuel to BSEN14214.



ESLP1200

| Capacity | Length | Width | Height |
|------------------------|---------|---------|---------|
| 1200 Ltrs/ 260 Gals | 1940 mm | 1540 mm | 1060 mm |



ES1225

| Capacity | Length | Width | Height |
|------------------------|---------|--------|---------|
| 1225 Ltrs/ 270 Gals | 2050 mm | 900 mm | 1515 mm |



ESSL1400

| Capacity | Length | Width | Height |
|------------------------|--------|--------|---------|
| 1400 Ltrs/ 307 Gals | 2200 | 650 mm | 1650 mm |



ES1800

| Capacity | Length | Width | Height |
|------------------------|---------|---------|---------|
| 1800 Ltrs/ 400 Gals | 2370 mm | 1300 mm | 1355 mm |



ESV2500

| Capacity | Diameter | Height |
|------------------------|----------|---------|
| 2500 Ltrs/ 550 Gals | 2000 mm | 1490 mm |



ES3500

| Capacity | Diameter | Height |
|------------------------|----------|---------|
| 3500 Ltrs/ 775 Gals | 2140 mm | 1945 mm |



ES9000

| 1 | | | | | | |
|---|-------------------------|----------|---------|--|--|--|
| | Capacity | Diameter | Height | | | |
| | 9000 Ltrs/ 1980 Gals | 2450 mm | 2950 mm | | | |



All dimensions are an approximate only.

Head Office

180 Gilford Road, Portadown, Co. Armagh, BT63 5LF United Kingdom

Tel: +44 (0) 28 3836 4444 Fax: +44 (0) 28 3836 4445 Emai: tankinfo@kingspan.co.uk www.kingspan.co.uk/oil

